

METRO



LIGHT BROWN MT06

PERFORMANCE

FLAMMABILITY:	Class 1 (ASTME-648)
SMOKE DENSITY:	Less than 450 (ASTME-662)
STATIC PROPENSITY:	Less than 3.5 kV (AATCC-134)
PROTECTIVE TREATMENT:	Sentry Plus® Soil and Stain Protector
ENVIRONMENTAL CERTIFICATIONS	
NSF/ANSI STANDARD 140-2007:	Gold Level IAQ
CRI GREEN LABEL™:	14148216
IAQ GREEN LABEL PLUS™:	\$216
CRI NUMBER:	GLP8216
CRI RATING:	HEAVY TRAFFIC
LEED:	May contribute to or comply with LEED credits MR 4.0, MR 5.0, IEQ 4.3 and innovation credit for NSF 140



WARRANTIES

Lifetime Limited Carpet Wear Warranty, Lifetime Limited Colorfastness to Indoor Light
Lifetime Static Warranty, 10 Year Stain Warranty
10 Year Limited Colorfastness to Atmospheric Contaminants Ideal for Heavy Commercial Use

TOLERANCE

One percent variance in bow, skew, and pattern elongation from breadth to breadth.
The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing.
Where seaming is necessary, a seam sealant must be used for all such installations.
Due to dyelot variations, actual material may vary slightly from the samples.
Chair pads are recommended to prevent premature wear of carpet.



LIGHT BROWN MT06



CHOCOLATE MT08



WOOD MT07



EARTH MT09

STYLE NAME:	Metro
CONSTRUCTION:	1/10" Tufted Textured Pattern Loop
FIBRE:	100% Colorstrand SD Nylon
DYED METHOD:	Solution Dyed
PILE WEIGHT:	ca745g/m ² (22oz/y ²)
TOTAL WEIGHT:	ca1765g/m ² (52oz/y ²)
PILE HEIGHT:	ca4.52mm
TOTAL HEIGHT:	ca6.8mm
STITCH RATE:	50.39 rows per 10cm
DENSITY:	4045
WEIGHT DENSITY:	80900
BACKING:	ActionBac®
PATTERN REPEAT:	4.0" (W) X 7.8" (L)
STANDARD ROLL SIZE:	3.66x45.72m



COFFEE MT10

MANUFACTURE IN USA

* AS IN ALL QUALITY CARPETS, COLOURS ARE SUBJECT TO DYELOT VARIATIONS.



ANB Furnishing Pte Ltd

No. 51, #01-12, Bukit Batok Crescent Unity Centre, Singapore 658077

Tel : 65-6569 3345, Fax : 65-6569 4544